


CFL

T3 Spiral

T3 SPIRAL 42W, 2700K




PRODUCT DESCRIPTION

EarthBulb's high lumen compact fluorescents easily replace incandescent light bulbs for nearly 75% energy savings. Savings over the long 8,000-10,000 hour average rated life eliminates 1050 lbs of CO² from being released into the air and saves \$73 on electricity (at 10¢/kwh) and provides an extended maintenance cycle. High lumen EarthBulbs may be used in table, floor and desk lamps, wall sconces and most general lighting applications. Electronic ballast provides for instant on, no flicker starting.

PRODUCT FEATURES

- Long 8,000 - 10,000 hour life lasts 13 times longer than incandescent.
- Small size easily replaces standard incandescent light bulbs.
- End of life circuitry protects against non passive failures.
- Medium (or "Edison") screw base is standard and fits most lamps.
- Lead free glass and a protective bulb wall coating before the phosphor is loaded in the tube provide excellent lumen maintenance.
- Not for sure on dimming circuits. Not for use in enclosed fixtures.

PRODUCT APPLICATIONS



MODEL NUMBER: ET42MSL

| Order Code | Pack Size | Individual UPC | Master Park UPC | Qty |
|---|-----------|--------------------|----------------------|-----|
| CF42SW1B | 1 | 8 11180010662 | 008 11180013854 | 12 |
| Dimensions (inches - Length x Width x Height) | | | | |
| CF42SW1B | 1 | 3.15 x 3.15 x 7.56 | 13.46 x 10.39 x 8.27 | 12 |
| Weight (lbs) | | | | |
| CF42SW1B | 1 | 0.4186 | 5.7498 | 12 |

| Electrical | |
|-----------------------|--|
| Watt | 42 |
| Input Current | 610 (mA) |
| Power Factor | >0.5 |
| Harmonic Distortion | < 150% |
| Crest Factor | < 1.70 |
| Voltage | 120 volt |
| Frequency | 60hz |
| Min. Start Temp | 0° F |
| Max. Operating Temp | 100° F |
| Base Type | Medium E26 |
| Light | |
| Initial Lumens | 2820 |
| Lumens per Watt | 68 |
| Color Temperature | 2700K |
| Color Rendering (CRI) | > 80 |
| Agency Approvals | |
| UL | Yes |
| Energy Star | No - Life Rated at 10,000 hrs |
| RoHS | Yes |
| FCC | Part 18, Subpart C |
| Product Details | |
| Warranty | 2 years Residential 1 year Commercial |
| Mercury Content | < 1.5 |
| Diameter | 2.76 |
| Overall Length | 7.01 |