LED PAR38

19 Watt 3000K PAR38 LED





Electrical					
Watt	19				
Input Current	178 (mA)				
Power Factor	0.95				
Voltage	120 volt				
Frequency	60hz				
Min. Start Temp	-4F				
Max. Operating Temp	104F				
Base Type	E26 Medium				
Light					
Initial Lumens	1250				
Lumens per Watt	66				
Color Temperature	3000K				
Color Rendering (CRI)	83				
Beam Angle	40°				
Agency Approvals					
UL	Yes				
Energy Star	40,000 hr rated				
RoHS	Yes				
FCC	Yes				
Product Details	Product Details				
Warranty	10 years, 6 hrs/day				
Mercury Content	0				
Diameter	4.72"				
Overall Length	5.12"				

PRODUCT DESCRIPTION

19 watt PAR38 EarthBulb LED floodlight replaces 120 watt incandescent floodlights for over 85% energy savings. 3000K color of light is standard. Great for use in dimming recessed lighting, track lighting and display lighting applications. High power LED and an advanced cooling system provides for 40,000 hours of LED life. Medium screw base.

PRODUCT FEATURES

- Dimming PAR38 flood light provides 1250 lumens, capable of dimming to less than 5%
- 40° beam angle provides a flood, not spot light
- · Lensed single chip design look like halogen when powered on
- Chipset provides 3000K white light with a high color rendering rating over 80
- · Wet rated UL and suitable for exterior locations

CONE OF LIGHT

Lumens: 1250 Diameter Distance Foot Candles fc ft ft 2 427.6 1.39 4 106.9 2.79 6 47.51 4.19 5.58 8 26.72 10 17.10 6.98


PRODUCT APPLICATIONS



LUMINOUS DISTRIBUTION INTENSITY DATA

Y(deg)	_				
	0	23	45	68	90
0	2663	2664	2663	2665	2663
5	2529	2531	2527	2517	2499
10	2154	2165	2162	2147	2121
15	1690	1704	1704	1690	1664
20	1199	1212	1216	1202	1178
25	772	781	787	778	763
30	445	451	453	451	440
35	246	246	246	249	247
40	144	142	143	146	148
45	89.8	88.8	89.5	91.9	93.3
50	60.7	60.5	16.2	62.5	63.2
55	43	43.1	43.5	44.1	44.6
60	32.6	32.4	32.7	33.1	33.3
65	24.9	24.9	25	25	25.1
70	19.3	19.3	19.3	19.3	19.2
75	14.4	14.4	14.4	14.4	14.3
80	8.86	8.89	8.82	8.77	8.64
85	3.75	3.79	3.74	3.69	3.59
90	0.03	0.07	0.08	0.07	0.05

LUMINOUS DISTRIBUTION INTENSITY DIAGRAM



AVERAGE BEAM ANGLE (50%):36.1°

Note: IES files available upon request.

MODEL NUMBER: L3FP3819DW

MODEL NOMBER: EST SOTSEN							
Order Code	Individual UPC	Master Park UPC	Qty				
L3FP3819301BDW	8 11180018705	008 11180018705	6				
Dimensions (inches)							
L3FP3819301BDW	5.12 x 5.12 x 6.69	10.82 x 16.26 x 7.31	6				
Weight (lbs)							
L3FP3819301BDW	1.034	7	6				



Individual





