

Project	
Date	
Prepared By	
Model No.	LP2550D8

Specifications

ELECTRICAL

Watts: 5
Input Current: 85 (mA)
Power Factor: 0.8
Voltage: 120 volt, 60Hz
Base Type:
 E26 Medium
Operation:
 Dimmable
Operating Temp. Range:
 -4°F to 104°F

LIGHT

Initial Lumens: 520
Lumens per Watt: 74
Color Temperature: 5000K
CRI: 80+
Beam Angle: 40°

AGENCY APPROVALS

UL/FCC : Yes
Energy Star: Yes
RoHs: Yes

PRODUCT DETAILS

Warranty: 10 years
Rated Life: 15,000 hrs.
Dimensions:
Length: 2.5"
Diameter: 3.35"



Norton Shores, Michigan 49441
 T: 231.332.1188 | F: 231.726.5029
 TOLL FREE: 866.632.7840
 www.earthtronics.com

LED PAR20

520 Lumen, 5 Watt, 5000K



ORDER CODE:

11579

MODEL NUMBER:

LP2550D8

OPERATION:

Dimmable

ENERGY STAR ID:

2396738

REBATE AVAILABILITY*

PRODUCT DESCRIPTION

5 watt PAR20 EarthBulb LED floodlight replaces 50 watt incandescent floodlights for over 80% energy savings. Great for use in dimming recessed lighting, track lighting and display lighting applications. High power LED and an advanced cooling system provides for 15,000 hours of LED life. Medium screw base. PAR20 can be used indoor or outdoor.

PRODUCT FEATURES

- + This PAR20 provides 520 lumens
- + dimming to less than 10%
- + Energy Star rated product
- + Suitable for damp locations
- + 5000K day light with a high color rendering rating 80+
- + 40° beam angle provides full radial illumination

PACKAGE DETAILS

INDIVIDUAL PACKAGE

Individual Carton Qty: 1
Dimensions:
 2.50" L x 2.50" L x 3.42" H
Weight: 0.462 LBS
UPC: 840791115794

INNER CARTON

Master Carton Qty: 12
Dimensions:
 10.55" L x 7.96" W x 3.93" H
Weight: 1.83 LBS
UPC: 84079111579400

APPLICATIONS

- + Recessed Can fixtures
- + Track Lighting
- + Display Lighting
- + Corridor Lighting
- + Large hanging pendants

MASTER CARTON

Master Carton Qty: 24
Dimensions:
 10.9" L x 8.30" W x 8.50" H
Weight: 7.78S LBS
UPC: 84079111579400

