

Project	
Date	
Prepared By	
Model #	AL150WSCCTBK5

## Specifications

### ELECTRICAL

**Watts:** 150

**Voltage:**

120/277VAC, 347VAC

**Power Factor:** 0.942

**THD:** 15.1%

**Operating Temp. Range:**

-40°C (-4°F) to 45°C (113°F)

**Dimming:** 0-10VDC Dim

**Capability & Range:**

Continuous down to 10%

### LIGHT

**Initial Lumens:** 19500

**Lumens per Watt:** 130

**Color Temperature:**

3000K, 4000K, 5000K

**CRI:** 73

### AGENCY APPROVALS

**UL/cUL:** Yes

**RoHS:** Yes

**IP65:** Yes

**DLC® Premium:** Yes

### PRODUCT DETAILS

**Housing:**

Die-cast aluminum alloy

**Warranty:** 5 years

**Weight:** 8.50 LBS

# LED Area Light

Color & Wattage Selectable 120/277VAC, 347VAC



### ORDER CODE:

11765

### MODEL NUMBER:

AL150WSCCTBK5

### LUMEN LEVEL:

9100 lumens - 70 watts

13000 lumens - 100 watts

19500 lumens - 150 watts

### DLC® PRODUCT ID:

S-T93CLS

### REBATE AVAILABILITY\*

## PRODUCT DESCRIPTION

EarthTronics color and wattage selectable LED Area Lights low profile design that provides the flexibility to insure the correct light level and color temperature desired in different applications. Select from 3000K, 4000K or 5000K color temperatures as well as 9100, 13000 or 19500 lumen levels. LED Area Lights are ideal for exterior illumination for commercial, industrial, and municipal facilities. The durable die cast aluminum housing is powder coated to maintain the fixture appearance for several years. The area light provides more than 130 lumens per watt efficient performance. A dusk to dawn sensor is available and is easily added at the time of installation. The design is built to withstand all climates and allows for an extreme temperature range, even operating down to -40 degrees C°, and is IP65 wet location rated. The unique changeable mount system includes the following options: slip fitter with adjustable angle, straight mounts for poles and wall applications and a trunnion (yoke) mount. DLC® Premium listed.

## PRODUCT FEATURES

- + Color Selectable: 3000K, 4000K, 5000K
- + Lumen Selectable: 9100, 13000 or 19500
- + Provides more than 130 lumens per watt
- + Die-cast aluminum alloy housing provides long life in commercial installations
- + Standard 6KV surge protector included (10KV optional upgrade available)
- + Driver standard with 0-10V dimming (prewired)
- + Corrosion resistant finish & screws
- + UV resistant powder coat finish
- + IP65 wet location rated
- + DLC® 5.1 Technical Requirement
- + Compatible with EarthConnect, Networked Lighting Controls


## APPLICATIONS

- + Parking Lots
- + Campuses
- + Area Lighting
- + Grocery Store
- + Walkways
- + Commercial

Please consult installation instructions for proper application and use of this fixture.

\*Rebate availability access it here: [www.earthtronics.com/rebate-finder](http://www.earthtronics.com/rebate-finder)

## PRODUCT DIMENSIONS:



## PACKAGE DETAILS

Dimensions: 17.99" x 11.81" x 4.72"


Weight: 8.50 LBS

UPC: 840791117651

Note: Mounting system ordered separately

## COLOR & WATTAGE SELECTION


Watt Selectable  
70W/100W/150W  
\*wattage options are  
indicated on label



Color selectable  
3000K/ 4000K/5000K  
\*color options are  
indicated on label


1. Take off the waterproof rubber cover from the wattage-box
2. Select the wattage using the slide switch. The watt options are indicated on the label.
3. Select the color temperature using the slide switch. The color options are indicated on the label.
4. Put back the waterproof rubber cover.

## OPTIONAL ACCESSORIES




Slip-Fitter

Order Code: 11767




Trunnion Mount

Order Code: 11769



Yoke

Order Code: 11770



Arm Mount

Order Code: 11768

- 10KV Surge Protector ————— Order Code: 11774
- Type 5 Lens ————— Order Code: 11773



Photocell Kit

Order Code: 11086  
for 120/277V use only

## COMPATIBLE WITH



Bluetooth® Mesh  
Multi-function Sensor & Node  
Plug-in sensor (Audio Jack) 12 VDC  
(sold separately)

Order Code: 11806

EarthConnect, Bluetooth® networked lighting control system makes it easy to maximize energy savings, achieve code compliance for indoor applications. It's simple and intuitive. Using the EarthConnect app, nodes can be commissioned without the need for a gateway or Internet access.

For more information visit:  
<https://www.earthtronics.com/product/earthconnect.com>

Easily access our DLC qualified products with rebates in your area.

ACCESS IT HERE: [Rebate Finder - LED Area Light](#)

[www.earthtronics.com/rebate-finder/catalog/](http://www.earthtronics.com/rebate-finder/catalog/)

